



Overview

Model Name	APC Back-UPS 600, 230V without Auto Shutdown Software, India
Includes	User Manual , Warranty card
Standard Lead Time	Usually in Stock
Product Distribution	India

Output

Output Power Capacity	360 Watts / 600 VA
Max Configurable Power (Watts)	360 Watts / 600 VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	47 - 63 Hz
Output Frequency (sync to mains)	Line Interactive
Waveform Type	Stepped approximation to a sinewave

Input

Nominal Input Voltage	230V
Input Frequency	47 - 63 Hz
Input Connections	India 3-pin 6A
Cord Length	1.22 meters
Input voltage range for main operations	145 - 290 V

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	6 hour(s)
Replacement Battery	APCRBC110

Communications & Management

Control panel	LED status display with On Line : On Battery : Replace Battery and Building Wiring Fault
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	255 Joules
---------------------	------------

Physical

Maximum Height	218.0 mm
Maximum Width	107.0 mm
Maximum Depth	237.0 mm
Net Weight	4.7 kg
Shipping Weight	5.2 kg
Shipping Height	295.0 mm
Shipping Width	165.0 mm
Shipping Depth	310.0 mm

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	0.000 dB

Conformance

Approvals	BIS Approved
Standard warranty	2 years repair or replace

Sustainable Offer Status

REACH	REACH: Contains No SVHCs
-------	--------------------------