



APC Smart-UPS 750VA USB & Serial 230V, India Specific

SUA750I-IN

Call for More Information 18001030011

- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
- Includes: CD with software, Smart UPS signalling RS-232 cable, USB cable, User Manual

Output	
Output power capacity	500Watts / 750VA
Max Configurable Power (Watts)	500Watts / 750VA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal
Topology	Line Interactive
Waveform type	Sine wave
Output Connections	(2) IEC Jumpers (Battery Backup) (6) IEC 320 C13 (Battery Backup)
Transfer Time	2ms typical

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14
Input voltage range for main operations	160 - 285V
Input voltage adjustable range for mains operation	151 - 302V

Batteries & Runtime	
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Communications & Management

Interface Port(s)	DB-9 RS-232, SmartSlot, USB
-------------------	-----------------------------

Physical

Maximum Height	157MM, 15.7CM
Maximum Width	137MM, 13.7CM
Maximum Depth	361MM, 36.1CM
Net Weight	13.18KG
Shipping weight	14.55KG
Shipping Height	290MM, 29.0CM
Shipping Width	270MM, 27.0CM
Shipping Depth	500MM, 50.0CM
Units per Pallet	24.0

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.